



SAMA di Santon Marinella

Via Volontari della Libertà, 48/c - 30034 Piazza Vecchia di Mira (VE) – ITALY

Tel./Fax +39 041 5676159

e-mail info@samastucchi.it

web site <http://samastucchi.it>

TECHNICAL DATASHEET for "STUCCO di ANTICHE TRADIZIONI"

- Description: natural non-synthetic stucco for interior decoration.
- Main Characteristics:
 - natural: absence of any acrylic or synthetic resin, composition is based on vegetal resins and pure baked quality linseed oils
 - rapid application: up to 7/8 square meters /hour of finished wall

OTHER CHARACTERISTICS

- Ready to use: no need to mix it with other products, not even to color it.
- Odorless: the total absence of synthetic resins leaves the stucco odorless, it can be applied in any season, even with closed windows.
- Transpiring: the totally natural composition does not affect the wall transpiration characteristics.
- Non toxic: acrylic resins are infact totally absent; in case of contact with the skin rinse with water, don't use synthetic thinners.
- Fireproof: beeing made with water and vegetal resins our tests confirm that it is fireproof; while the fire-resistance classification has not yet been certified, we estimate that the "Stucco di Antiche Tradizioni" will be certified to comply with class 0 (maximum fire resistance).
- Working temperature: above 5 °C.
- Tools: stainless steel rectangular trowel.
- Tools Cleaning: plain water.
- Directions for Use: apply above the special background "Primo" (see specific datasheet). Apply one opaque coat of Antiche Tradizioni, without any polishing action; after one hour apply a second coat.
- Drying: 6/8 hours, depending on temperature and humidity.
- Color: all shades available for the Stucco Madreperlato; the final result is always medium polished.
- Polishing process: the "Stucco di Antiche Tradizioni" does not need to be treated with any kind of wax. The best shining effect is obtained applying the second coat for only 3-4 sqm. and then repeatedly passing over with the clean stainless steel trowel while the stucco is drying up. Once dryed up, the shining effect can't be increased. Use the trowel during the polishing action exactly like during the application action;



SAMA di Santon Marinella

Via Volontari della Libertà, 48/c - 30034 Piazza Vecchia di Mira (VE) – ITALY

Tel./Fax +39 041 5676159

e-mail info@samastucchi.it

web site <http://samastucchi.it>

there is no need to use it diagonally from bottom to top like generally done with synthetic products.

- Repeated applications: if the next day after the stucco application you need to correct part of the walls with a stronger color shade, it can be done normally even if the wall has already received the polishing treatment, without re-preparing it with sandpaper.
- Repairable: in case of damages or wall cracks, the coat of "Stucco di Antiche Tradizioni" can be repaired.
- Maintenance: for cleaning use only alcohol at 94 C proof or higher.
- Yield: 20/24 sqm/liter.
- Manpower: 7/8 sqm/hour of finished wall.
- Shelf life: unlimited in a fresh room closed in the original container. If part of the content has been used, close carefully the container and the remainder will still be usable for long time.

IMPORTANT NOTE

No special tool or technique is required to remove the "Stucco di Antiche Tradizioni": 2 coats of standard paint are enough to cover the wall.