



SAMA di Santon Marinella

Via Volontari della Libertà, 48/c - 30034 Piazza Vecchia di Mira (VE) – ITALY

Tel./Fax +39 041 5676159

e-mail info@samastucchi.it

web site <http://samastucchi.it>

TECHNICAL DATASHEET of the "SPRAYED BACKGROUND for MADREPERLATO"

- Description: specific background for the Stucco Madreperlato.
- Main Characteristics:
 - special formulation for sprayed application allows significant time savings and guarantees better results on curved and irregular surfaces like columns, stepped ceilings, and speeds the application on very large surfaces
 - very easy application

OTHER CHARACTERISTICS

- Ready to use: add 50% of plain water
- Non toxic: acrylic resins are infact totally absent.; in case of contact with the skin rinse with water, don't use synthetic thinners.
- Working temperature: above 5 °C..
- Tools: spray-gun, nozzle 1.7 mm, at 3 atmospheres pressure.
- Tools Cleaning: plain warm water.
- Directions for Use: first prepare the wall with one coat of Plaster for Large Surfaces (see specific datasheet). Once dried up (after 1 or more hours) smooth with sandpaper #180/220 and remove the dust from the wall with a dry brush. Apply the watered-down stucco with the spray-gun. If the surface is very porous a second coat can be sprayed after intermediate use of sandpaper (and dust removal).
- Drying: wait one hour at 18 C between layers; wait 2-3 hours for complete drying. Time intervals change with temperature, humidiy and background characteristics.
- Colour: white, can be tinted with universal colors.
- Yield: 10 sqm / liter of diluted product.
- Shelf life: 3/4 years in a fresh room closed in the original container.