



**SAMA** di Santon Marinella

Via Volontari della Libertà, 48/c - 30034 Piazza Vecchia di Mira (VE) – ITALY

Tel./Fax +39 041 5676159

e-mail [info@samastucchi.it](mailto:info@samastucchi.it)

web site <http://samastucchi.it>

## **TECHNICAL DATASHEET of the "NUOVO STUCCO LUCIDO VENEZIANO WATERPROOF "**

- Description: stucco for interior decoration.
- Main Characteristics:
  - easy application: our new formula for the Stucco Lucido Veneziano no longer requires the usual 4/5 coats to achieve the desired final effect. With just two coats, the “filling” coat and the “polishing” coat, you will create the Stucco Lucido special effects.
  - waterproof: wall treated with this stucco can be cleaned with water and liquid soap.

### **OTHER CHARACTERISTICS**

- Ready to use: if needed add just some plain water
- Fireproof: the product is based like our totally natural products on gypsum and water, with a minor content of synthetic resins to add the waterproof features. Our tests indicate that it is fully fireproof. We estimate that the "Nuovo Stucco Lucido Veneziano Waterproof" will be certified to comply with class 0 (maximum fire resistance).
- Working temperature: above 5°C.
- Tools: stainless steel triangular or rectangular trowel. The tools size can be changed according to each application requirements.
- Tools Cleaning: plain water.
- Directions for Use: apply 1/2 coats of “Plaster for Large Surfaces” (see specific datasheet) depending on wall porosity. Let it dry up for about 1 hour, smooth with sandpaper n. 180/220 and remove the dust with a dry brush. This operation can be repeated between the first and second coat. After a couple of hours apply one coat of “Background for Waterproof” (see specific datasheet). When dried up apply the first “filling” coat of “Nuovo Stucco Lucido Veneziano Waterproof” touching the wall with spots about 10/15 cm apart until about 1 sqm is covered. Go back to the beginning and touch more spots until the surface is completely covered. Once this part of the wall is fully done, clean the trowel and pass the surface to remove any stucco running.
- Hints: apply leaving a very thin layer.
- Drying: 2/4 hours, depending on temperature and humidity.
- Colour: white, can be tinted with universal colors; the final effect is very shining
- Polishing process: after about 4 hours (depending on climatic conditions) when the stucco is dry, apply the second “polishing” coat with the same technique used for the “filling” coat, then when 2-3 square meters are covered, while the stucco is still wet,



*SAMA di Santon Marinella*

Via Volontari della Libertà, 48/c - 30034 Piazza Vecchia di Mira (VE) – ITALY

Tel./Fax +39 041 5676159

e-mail [info@samastucchi.it](mailto:info@samastucchi.it)

web site <http://samastucchi.it>

polish the surface repeatedly passing over the surface with a clean trowel, until the desired shining effect is achieved.

- Maintenance: for cleaning use only water and a mild liquid soap; wait at least three days from the application; don't use any type of alcoholic cleaning product.
- Yield: 4-5 sqm / liter, including both coats (filling and polishing).
- Manpower: 4 sqm of finished wall / day (8 hours)
- Shelf life: unlimited in a fresh room closed in the original container.

**IMPORTANT NOTE**

- no special tool or technique is required to remove the "Nuovo Stucco Lucido Veneziano Waterproof": 2 coats of standard paint are enough to cover the wall
- never use alcohol to clean the walls treated with the "Nuovo Stucco Lucido Veneziano Waterproof"