



SAMA di Santon Marinella

Via Volontari della Libertà, 48/c - 30034 Piazza Vecchia di Mira (VE) – ITALY

Tel./Fax +39 041 5676159

e-mail info@samastucchi.it

web site <http://samastucchi.it>

TECHNICAL DATASHEET of the "STUCCO MARMORINO PLUS"

- Description: natural stucco for interior decoration.
- Main Characteristics:
 - natural: absence of any acrylic or synthetic resin, composition is based on vegetal resins and pure baked quality linseed oils; this composition makes our stucco much more easy to work than similar products
 - super-shine: the Marmorino Plus +gives a mirror-like surface
 - quick application: 4/5 sqm/hour of finished wall

OTHER CHARACTERISTICS

- Ready to use: no need to mix it with other products.
- Odorless: it can be applied in any season, even with closed windows.
- Transpiring: the totally natural composition does not affect the wall transpiration characteristics.
- Non toxic: acrylic resins are infact totally absent; in case of contact with the skin rinse with water, don't use synthetic thinners.
- Fireproof: beeing made with water and vegetal resins our tests confirm that it is fireproof; estimate that the "Stucco Marmorino Plus" will be certified to comply with class 0 (maximum fire resistance).
- Working temperature: above 5°C.
- Tools: stainless steel rectangular trowel. The tools size can be changed according to each application requirements.
- Tools Cleaning: plain water.
- Directions for Use: smooth the surface with the "Plaster for Large Surfaces" (see specific datasheet); let each coat of plaster dry up for about 1 hour, smooth with sandpaper n. 180/220 and remove the dust with a dry brush. When dried up apply the first coat of "Stucco Marmorino Plus" touching the wall at will with wide spots, and carefully removing any stucco runnings with a clean tool. After about 4 hours apply the second coat of Marmorino, using the same technique.
- Hints: apply in spots and remove the stucco completely leaving no thickness.
- Drying: 6/8 hours, depending on temperature and humidity.
- Colour: white and 7 base colours, that can be freely mixed: Lemon Yellow, Mint Green, Tropical Yellow, Smoke Gray, Venetian Red, Sky Blue, Tobacco; the final effect is mirror-like.



SAMA di Santon Marinella

Via Volontari della Libertà, 48/c - 30034 Piazza Vecchia di Mira (VE) – ITALY

Tel./Fax +39 041 5676159

e-mail info@samastucchi.it

web site <http://samastucchi.it>

- Polishing process: the best shining effect is obtained applying the second coat for 3/4 sqm, and while the stucco is still wet, polish the surface repeatedly passing over the surface with a clean trowel, until the desired shining effect is achieved. Use the trowel during the polishing action exactly like during the application action; there is no need to use it diagonally from bottom to top like generally done with synthetic products. The shining effect of the Marmorino Plus can be increased even the day following the application, repeating the polishing process with the clean trowel.
- Repeated applications: if the next day after the stucco application you need to correct part of the walls with a stronger color shade, it can be done normally even if the wall has already received the polishing treatment, without re-preparing it with sandpaper.
- Repairable: in case of damages or wall cracks, the coat of " Marmorino Plus" can be easily repaired.
- Maintenance: for cleaning use only alcohol at 94 C proof or higher.
- Yield: 18-20 sqm / liter.
- Manpower: 4-5 sqm/hour of finished wall.
- Shelf life: unlimited in a fresh room closed in the original container. If part of the content has been used, close carefully the container and the remainder will still be usable for long time.

IMPORTANT NOTE

No special tool or technique is required to remove the "Stucco Marmorino Plus": 2 coats of standard paint are enough to cover the wall.