



SAMA di Santon Marinella

Via Volontari della Libertà, 48/c - 30034 Piazza Vecchia di Mira (VE) – ITALY

Tel./Fax +39 041 5676159

e-mail info@samastucchi.it

web site <http://samastucchi.it>

TECHNICAL DATASHEET of the "PASTE STUCCO for COLOURED WOOD"

- Description: specific stucco for wood repair.
- Main Characteristics:
 - The formulation based on natural vegetal resins gives it exceptional plasticity and viscosity characteristics; it is the ideal solution for the restoration of any wood artwork, doors, windows, to fill holes and cracks

OTHER CHARACTERISTICS

- Ready to use: if needed add just some plain water
- Odorless: it can be applied in any season, even with closed windows.
- Non toxic: acrylic resins are infact totally absent.; in case of contact with the skin rinse with water, don't use synthetic thinners.
- Working temperature: no practical limit.
- Tools: as needed.
- Tools Cleaning: plain water.
- Directions for Use: carefully clean the damaged surface and apply a first very thin layer. Apply several layers as needed, waiting at least two to four hours in between (at 18°C). After complete drying it will be easily smoothed with sandpaper.
- Hints: clean thoroughly the damaged surface, apply thin layers, respect the drying times.
- Drying: it will be completely dried up after three to five hours at 18°C. Time intervals change with temperature, humidity and background characteristics.
- Colour: fir, pine, medium walnut, dark walnut, dark duglas, mahogany. For technical reasons the colour shades from different production batches will not be exactly identical.
- Yield: changes with type of wood and of damage.
- Shelf life: 3/4 years in a fresh room closed in the original container.

IMPORTANT NOTE

After complete drying the surfaces can be worked on with waxes, water-based, alcohol-based, solvent-based and impregnating paints